

## Cisco Model DPC3000 DOCSIS 3.0 Cable Modem

The Cisco Model DPC3000™ DOCSIS® 3.0 Cable Modem (DPC3000) provides DOCSIS broadband service providers with a cost-effective solution for delivering high-speed bi-directional data services. The DPC3000 provides a faster connection to the Internet by incorporating four bonded downstream channels along with four bonded upstream channels. These bonded channels deliver downstream data rates in excess of 160 Mbps and upstream data rates up to 120 Mbps, up to four times faster than conventional single-channel DOCSIS 2.0 cable modems.<sup>1</sup>

The DPC3000 is designed to meet DOCSIS 3.0 specifications as well as offering backward compatibility for operation in DOCSIS 2.0, 1.1 and 1.0 networks.

The DPC3000 also features WebWizard, a browser-based user interface. WebWizard is a powerful tool that facilitates installation and troubleshooting and eliminates the need to load set-up software on the customer premises equipment (CPE).

**Figure 1.** Cisco Model DPC3000 DOCSIS 3.0 Cable Modem



### Features

#### DOCSIS

- Four (4) bonded channels with total throughput in excess of 160 Mbps
- Designed to meet DOCSIS 3.0 specifications as well as backward compatibility with existing DOCSIS 2.0, 1.1 and 1.0 networks
- Enhanced packet processing technology to maximize performance

#### Connections

- Bridged 1000/100/10 Mbps Ethernet port with Auto-negotiate and Auto-MDIX and USB 2.0 data port
- Support for up to 64 users (1 USB port user and up to 63 users on user-supplied Ethernet hubs)

<sup>1</sup> Channel Bonded cable modems must be used in conjunction with CMTSs that support Channel Bonded bonding per the DOCSIS 3.0 specifications. When used with non-Channel Bonded CMTSs, Channel Bonded cable modems function as a conventional DOCSIS 2.0 cable modems.

**Design and Function**

- Attractive compact design and versatile orientation to stand vertically, lie flat on the desktop or shelf, or mount easily on a wall
- LED status indicators on the front-panel provide an informative and easy-to-understand display that indicates the cable modem operational status and real-time data transmission activity
- Rugged electronic components for long-term reliability

**Management**

- Software upgradeable by network download
- Remote manageability using SNMP V1/V2 and V3

**Software and Documentation**

- CD-ROM containing user guide and USB driver installation software for Microsoft Windows Vista, Windows XP, and Windows 2000 operating systems

**Figure 2.** Cisco Model DPC3000 DOCSIS 3.0 Cable Modem Front Panel



**Table 1.** Front Panel Features

Feature	Description
Indicators	POWER, DS, US, ONLINE, LINK
Color	Charcoal gray, black face plate, silver text, green LEDs
Branding	Cisco and model number

**Figure 3.** Cisco Model DPC3000 DOCSIS 3.0 Cable Modem Back Panel



**Table 2.** Back Panel Features

Feature	Description
Connections In	CABLE, POWER
Connections Two-Way	ETHERNET, USB
Power Input	AC power adapter 12 VDC
Label	Cable Modem MAC Address
Reboot	Reset-to-Factory Default Momentary Switch (Factory Reset)

### Ordering Information

**Table 3.** Ordering Information

Description Hardware Revision 1.0 (42/88 MHz Diplex Filter)	
North American Tuning Plan (NTSC-STD and NTSC-HRC)	Part Number
DPC3000 Channel Bonded Cable Modem for North American NTSC tuning plan. Includes: <ul style="list-style-type: none"> <li>• DOCSIS 3.0 Cable Modem, 4 DS X 4 US</li> <li>• NTSC frequency plan</li> <li>• 5-42/88-1000 MHz diplex filter (DOCSIS)</li> <li>• GigE port</li> <li>• USB 2.0 port</li> <li>• 12 VDC/1A, 100-120 VAC / 50-60 Hz, desktop style high efficiency linear-switching power supply</li> <li>• Ethernet cable</li> <li>• USB cable</li> <li>• CD-ROM</li> </ul> <b>North America</b>	4021386
DPC3000 Channel Bonded Cable Modem for North American NTSC tuning plan. Includes: <ul style="list-style-type: none"> <li>• DOCSIS 3.0 Cable Modem, 4 DS X 4 US</li> <li>• NTSC frequency plan</li> <li>• 5-42/88-1000 MHz diplex filter (DOCSIS)</li> <li>• GigE port</li> <li>• <b>No USB 2.0 port</b></li> <li>• 12 VDC/1A, 220 VAC / 50-60 Hz, wall-mount style high efficiency linear-switching power supply for Korea</li> <li>• Ethernet cable</li> <li>• CD-ROM</li> </ul> <b>Korea</b>	4021388

International Tuning Plan (PAL-B, PAL-G, and NTSC)	Part Number
<p>DPC3000 Channel Bonded Cable Modem for North American NTSC tuning plan. Includes:</p> <ul style="list-style-type: none"> <li>• DOCSIS 3.0 Cable Modem, 4 DS X 4 US</li> <li>• International frequency plan</li> <li>• 5-42/88-1000 MHz diplex filter (DOCSIS)</li> <li>• GigE port</li> <li>• USB 2.0 port</li> <li>• 12 VDC/1A, 230 VAC / 50-60 Hz, wall-mount style high efficiency linear-switching power supply for Australia</li> <li>• Ethernet cable</li> <li>• USB cable</li> <li>• CD-ROM</li> </ul> <p><b>Australia</b></p>	<p>4021389</p>

Description Hardware Revision 1.01 (5-55/88-1000 MHz Diplex Filter)	
Japanese Tuning Plan (NTSC-Japan)	Part Number
<p>DPC3000 Channel Bonded Cable Modem for North American NTSC tuning plan. Includes:</p> <ul style="list-style-type: none"> <li>• DOCSIS 3.0 Cable Modem, 4 DS X 4 US</li> <li>• Japanese frequency plan</li> <li>• 5-65/88-1000 MHz diplex filter (DOCSIS)</li> <li>• GigE port</li> <li>• <b>No USB 2.0 port</b></li> <li>• 12 VDC/1A, 100-120 VAC / 50-60 Hz, desktop style high efficiency linear-switching power supply</li> <li>• No data cables</li> <li>• Printed Japanese user guide</li> </ul> <p><b>Japan – Importer specific configuration</b></p>	<p>4021387</p>
<p>DPC3000 Channel Bonded Cable Modem for North American NTSC tuning plan. Includes:</p> <ul style="list-style-type: none"> <li>• DOCSIS 3.0 Cable Modem, 4 DS X 4 US</li> <li>• Japanese frequency plan</li> <li>• 5-65/88-1000 MHz diplex filter (DOCSIS)</li> <li>• GigE port</li> <li>• <b>No USB 2.0 port</b></li> <li>• 12 VDC/1A, 100-120 VAC / 50-60 Hz, desktop style high efficiency linear-switching power supply</li> <li>• Ethernet Cable, 2 meter</li> <li>• Printed Japanese user's guide</li> </ul> <p><b>Japan – Importer specific configuration</b></p>	<p>4022944</p>

## Replacement Components

**Table 4.** Replacement Components

AC Power Supplies	Part Number
<i>High Efficiency Linear Switching, Class 2</i>	
100-120 VAC / 50-60 Hz, 12 VDC/1A desktop style high efficiency linear switching power supply for North America and Japan	4020982
100-120 VAC / 50-60 Hz, 12 VDC/1A wall-mount high efficiency linear switching power supply for North America and Japan (ICS importer markings)	4015452
100-120 VAC / 50-60 Hz, 12 VDC/1A wall-mount high efficiency linear switching power supply for North America and Japan (NOS importer markings)	4020519
220 VAC / 50-60 Hz, 12 VDC/1A wall-mount high efficiency linear switching power supply for Argentina	4015457
220 VAC / 50-60 Hz, 12 VDC/1A wall-mount high efficiency linear switching power supply for Korea	4015458
230-240 VAC / 50-60 Hz, 12 VDC/1A wall-mount high efficiency linear switching power supply with Euro plug	4015453
230-240 VAC / 50-60 Hz, 12 VDC/1A wall-mount high efficiency linear switching power supply with United Kingdom style plug	4018794
230-240 VAC / 50-60 Hz, 12 VDC/1A wall-mount high efficiency linear switching power supply for Australia	4018797
<i>Switching Mode, Class 2</i>	
100-240 VAC / 50-60 Hz, 12 VDC/1A desktop universal switching mode power supply, Class II, C7 AC connector, 2 conductor (power cord not included, order power cord separately)	4009116
Power Cords	Part Number
<i>Class 2</i>	
Power cord, 2 conductor, North America, NEMA 1-15 to C7, non-polarized	1002239
Power cord, 2 conductor, Japan, NEMA 1-15 to C7, non-polarized	207586
Power cord, 2 conductor, European, Euro plug CEE7/16 to C7	503414
Power cord, 2 conductor, United Kingdom, BS1363 to C7	1002798
Power cord, 2 conductor, Brazil Euro plug CEE7/16 to C7, INMETRO	4009115
Power cord, 2 conductor, Korea	4010439
Power cord, 2 conductor, Argentina	4012938
Cables	Part Number
Ethernet cable, standard 1.2 meter length	740580
Ethernet cable, 2 meter	4018790
USB cable	740579
User Guide and USB Drivers	Part Number
CD-ROM with user guide and USB drivers	4023779



Scientific Atlanta is a registered trademark of Scientific-Atlanta, Inc.

DPC3000 is a trademark of Scientific-Atlanta, Inc.

Cisco, the Cisco logo, and Cisco Systems are trademarks or registered trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

DOCSIS is a registered trademark of Cable Television Laboratories, Inc.

*All other trademarks shown are trademarks of their respective owners.*

Specifications and product availability are subject to change without notice.

© 2007 Scientific-Atlanta, Inc. All rights reserved.

Scientific-Atlanta, Inc.

1-800-722-2009 or 770-236-6900

[www.scientificatlanta.com](http://www.scientificatlanta.com)

Part Number 7007798 Rev B

December 2007